CABLE FIXING ACCESSORIES

A range of adhesive and non-adhesive fixing methods for securing heating cable into position


MISCELLANEOUS ACCESSORIES



FT/HTP

A self-extinguishing conformable PVC adhesive tape. Used for low temperature heaters and applications only.


Dimensions:	12mm wide x 33m roll.
Max Withstand Temperature:	80°C.
Min Application Temperature:	0°C.
Adhesive:	Rubber resin.



FT/HTS

A glass cloth based adhesive fixing tape. Used for medium temperature heaters and applications. Designed for long term performance and resistance to continuous temperature exposure.


Dimensions:	12mm wide x 50m roll.
Max Withstand Temperature:	130°C.
Min Application Temperature:	0°C.
Adhesive:	Thermosetting rubber.



FT/PGL

A non-adhesive woven glass yarn fixing tape. High tensile strength, good resistance to chemicals. Used for high temperature heaters and applications.

Dimensions:	25mm wide x 50m roll.
Max Withstand Temperature:	500°C (short term).
Min Application Temperature:	0°C.
Adhesive:	None.



FT/ALUM


A 30 micron aluminium foil, coated one side with acrylic, pressure sensitive adhesive. The tape is backed with a strong polythene coated release paper. Flame retardent and water resistant.

Dimensions:	75mm wide x 45m roll.
Max Withstand Temperature:	110°C.
Min Application Temperature:	0°C.

FT/ALUM/100

A 100 micron soft tempered bright aluminium foil. Coated with a high tack pressure sensitive adhesive with UV light resistance.

Dimensions:	75mm wide x 50m roll.
Temperature Range:	-30°C to +130°C.



PPS/G


Pre-punched galvanised fixing strip for various applications holding heating cables in position on tanks and large surface areas etc.

Dimensions:	20mm wide x 25m roll.
Material:	Galvanised mild steel.



FB/GT

Stainless steel fixing bracket complete with 2 x nylon tie wraps, with several functions. Used in wide gutters to provide equal spacing for double runs of GT heating cable. Also used to protect heating cable in difficult transition zones and supporting heating cable in drainpipes.



FC/GT

Metallic fixing clip with self-adhesive pad. Used for securing GTe heating cable to gutter or roof surface. (Gutter surface must be clean and grease free).

Dimensions:	116mm x 18mm x 0.5mm.
Material:	Alloy.

HEAT TRACE™ SETTING THE STANDARDS LEADING THE WAY
45 Years 1974 - 2019

Heat Trace Ltd, Mere's Edge, Chester Road, Helsby, Frodsham, Cheshire, WA6 0DJ, England.
Tel: +44 (0)1928 726451 Fax: +44 (0)1928 727846
www.heat-trace.com Email: info@heat-trace.com

The information given herein, including drawings, illustrations and schematics (which are intended for illustration purposes only),is believed to be reliable. However, Heat Trace Ltd makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Users of Heat Trace Ltd products should make their own evaluation to determine the suitability of each such product for specific applications. In no way will Heat Trace Ltd be liable for any damages arising out of the misuse, resale or use of the product.

ANDS0506 (09102019) Issue 1